

eXR 6050 Touring

MATTE BLACK/CHROME SILVER



E-TOUR / CROSS

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS E6100, 36V, 250W, 60Nm
BATTERY	DARFON, 36V, 504 Wh, integrated
DISPLAY	SHIMANO SC-E5000, Clamp band
CHARGER	DARFON 2A Smart Plus charger
MAX SUPPORT SPEED	25km/h
CHARGE CYCLES	1000/60% of original capacity
DISTANCE RANGE	185km (ECO mode)

BENEFITS

- Shimano Steps E6100 motor: 250 W and 60 Nm
- Fully integrated 504 Wh battery ensures a range over 150 km*
- E-TUBE PROJECT: customized motor setting via the E-Tube Shimano application
- Simple and intuitive gear shifting with a 1x9 setup
- Wider 2" tires deliver maximum off-road comfort and safety
- ICR (Internal Cable Routing): clean, modern looks without visible cables
- Block Lock headset: frame protected against damage by handlebars
- Fully equipped, with a cargo rack, mudguards, kickstand, chain guard, night lights, and lock

GEOMETRY

FRAME SIZE	17" (M)	19" (L)	21" (XL)
WHEEL SIZE	28	28	28
SEAT TUBE LENGTH (MM)	431	482	533
SEAT TUBE ANGLE (DEGREE)	73.5	73.5	73.5
EFFECTIVE TOP TUBE LENGTH (MM)	590	610	630
REACH (MM)	409	429	449
STACK HEIGHT (MM)	610	610	610
HEAD TUBE LENGTH (MM)	130	130	130
HEAD TUBE ANGLE (DEGREE)	68	68	68
CHAINSTAY LENGTH (MM)	450	450	450
BB DROP (MM)	60	60	60
WHEELBASE (MM)	1127	1146	1167
HANDLEBAR WIDTH (MM)	680	680	680
STEM LENGTH (MM)	60	80	80
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	350

FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, SHIMANO STEPS ready, NEW integrated battery, Inner Cable Routing
HEAD SET	ACROS AZF-604, ZS56/28.6 ZS56/40; BlockLock 120°
FORK	SR Suntour NEX-E25NLO, Tapered, Coil, QR Type, 63mm travel
COLOUR	MATTE BLACK/CHROME SILVER
SIZES	17" (M), 19" (L), 21" (XL)

DRIVETRAIN

GEARS	1x9
SHIFTER	SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	ONE1 ET39-F13-SML-L/R, 38T
CASSETTE	SHIMANO CS-HG200-9, 11-36T
CHAIN	KMC E9s
PEDALS	VP Components VP-836

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-320BT, 3° upsweep, 15° backsweep, 20mm rise, 680mm, 31.8mm
STEM	ONE1 Python Alloy, 31.8mm, Adjustable
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Sport Alloy, SP C255, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J26S, 32H
TIRES	Schwalbe G-One Bite, 28x2.00", reflective tape
SPOKES	Sapim Galvanized Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country